



---

## Highlights

- IBM® Power Systems™ S914 server easily integrates into your organization's cloud & cognitive strategy and delivers superior price performance for your mission critical workloads.
  - Gain insights faster from your data with up to 1 TB memory
  - Designed for security, reliability and performance to face current and future security threats
  - Live partition mobility capabilities help you migrating from previous Power Systems.
  - Extend IBM i, a truly integrated operating system, and connect to the cognitive capabilities of the IBM Cloud using secure APIs
  - Save on licensing cost with strongest per core performance in the industry
- 

# IBM Power System S914

*Future forward infrastructure for your mission critical data*

## IBM Power Systems S914

IBM Power Systems S914 server easily integrates into your organization's cloud & cognitive strategy and delivers superior price performance for your mission critical workloads.

The next generation of IBM Power Systems, with POWER9™ technology, is built with innovations that deliver unprecedented security and reliability for data intense workloads of today's enterprises. POWER9 is designed from the ground up for data intensive workloads like Databases or Analytics. This new server generation comes along with twice the memory footprint than POWER8® making it an ideal platform for in-memory and data centric applications. Changes in the memory subsystem and the use of Industry Standard Memory DIMMs take POWER9 to the next level of price/performance leadership. Designed to run commercial, cognitive and database workload better than any other competitive Server Platform, customers are trusting POWER Servers as the robust and secure backbone of their IT infrastructure. Most of the Fortune 500 companies are using POWER technology in their IT infrastructure down from the shop level to large Datacenter deployments.

The IBM Power System S914 server (9009-41A) is a powerful 1-socket server that ships with up to eight activated cores and I/O configuration flexibility to meet today's growth and tomorrow's processing needs.

The server features:

- The following fully activated IBM POWER9 processor module configurations in a 19-inch rack-mount, 4U (EIA units) form factor.
  - 4-core Typical 2.3 to 3.8 GHz (max) POWER9 Processor
  - 6-core Typical 2.3 to 3.8 GHz (max) POWER9 Processor
  - 8-core Typical 2.8 to 3.8 GHz (max) POWER9 Processor (rack-mount configuration only)



**Systems  
Data Sheet**

- Up to 1024 GB of DDR4 memory
- Storage backplane options:
  - Eighteen SFF-3 Bays/Dual IOA with Write Cache
  - Twelve SFF-3 Bays/RDX Bays
  - Split feature to 6+6 SFF Bays: Add a second SAS Controller
  - Twelve SFF-3 Bays/RDX Bay/2 EXT PT
- Optional PCIe3 NVMe carrier card with two M.2 module slots
- Expansion capabilities for the EXP24SX SFF Gen2 bay Drawer
- Hot-swap PCIe Gen4 and Gen3 slots
- Integrated:
  - Service processor
  - EnergyScale technology
  - Hot-swap and redundant cooling
  - USB 3.0 ports
  - Two HMC ports
  - One system port with RJ45 connector
- Two hot-plug, redundant power supplies
- 19-inch rack-mounting hardware (4U) and tower option



*The new S914 - The entry offering into the POWER9 family of servers. Industry leading integrated security and reliability as well cloud enabled out of the box with PowerVM technology*

**Power System S914 (9009-41A) at a glance**

**System configurations**

Microprocessors	1x POWER9 CPUs 4, 6, 8 cores
Level 2 (L2) cache per core	512 K
Level 3 (L3) cache per core	10 MB
RAM (memory)	Up to 1 TB, from 16 DDR4 IS DIMM @ 2666, 2400, and 2133 Mhz, (IBM i in p05 SW tier up to 64GB)
Internal disk storage	12 or 18 SFF SAS Bay options (HDD or SDD), 2 internal PCIe G3 Slots for Storage Controller or NVMe
Processor-to-memory bandwidth	Up to 170 GB/s per socket
L2 to L3 cache bandwidth	7 TB/s on chip bandwidth
Media bays	optional RDX drive with 12 SFF Bay option only,
Adapter slots	13 x16 Gen4 full-height, half-length (CAPI) 12 x8 Gen4 full-height, half-length (with x16 connectors) (CAPI) 2 x8 Gen3 full-height, half-length (with x16 connectors) 4 x8 Gen3 full-height, half-length (one of these slots is used for the required base LAN adapter)

---

**Power System S914 (9009-41A) at a glance**

**Standard features**

I/O ports	<ul style="list-style-type: none"> <li>• One front USB 3.0 ports</li> <li>– Two rear USB 3.0 ports</li> <li>– Two HMC 1GbE RJ45 ports</li> <li>– One system port with RJ45 connector</li> <li>– 1x USB 3.0 front, 2x USB 3.0 rear, 2x HMC 1 GB Eth RJ45 ports, one system port with RJ45 connector, 2x High Speed 25 Gb/s ports</li> </ul>
-----------	--

**Connectivity support (optional)**

Advanced POWER Virtualization	PowerVM Enterprise integrated
RAS features	<p>Processor instruction retry            Selective dynamic firmware updates            Chip kill memory            ECC L2 cache, L3 cache            Service processor with fault monitoring            Hot-swappable disk bays            Redundant cooling fans</p>
Operating systems	<p>AIX 7.2 TL2            AIX 7.2 TL0, TL1 (P8 Compatibility Mode)            AIX 7.1 TL4, TL5 (P8 Compatibility Mode)            AIX 6.1 TL9 (P7 Compatibility Mode)            IBM i 7.3 TR4            IBM i 7.2 TR8            Ubuntu 16.04.4 LTS (P8 Compatibility Mode)            RedHat RHEL 7.4 LE (P8 Compatibility Mode)            SuSE SLES 11 SP4 (P8 Compatibility Mode)            SuSE SLES 12 SP3</p>
Power requirements	<ul style="list-style-type: none"> <li>• Operating voltage:               <ul style="list-style-type: none"> <li>– 900 W PSU: 100 - 127 V AC or 200 - 240 V AC</li> <li>– 1400 W PSU: 200 - 240 V AC</li> </ul> </li> <li>• Operating frequency: 47/63 Hz</li> </ul>
System dimensions	<p>19-inch rack-mount hardware</p> <ul style="list-style-type: none"> <li>• Width: 482 mm (18.97 in.)</li> <li>• Depth: 769.6 mm (30.3 in.)</li> <li>• Height: 173.3 mm (6.8 in.)</li> <li>• Weight: 36.3 kg (80 lb)</li> </ul> <p>Tower hardware:</p> <ul style="list-style-type: none"> <li>• Width: 182.4 mm (7.18 in.)</li> <li>• Width with stand: 328.5 mm (12.93 in.)</li> <li>• Depth: 751.7 mm (29.59 in.)</li> <li>• Depth with front-rotatable door: 814.7 mm (32.07 in.)</li> <li>• Height: 486.1 mm (19.14 in.)</li> <li>• Height with handle: 522 mm (20.55 in.)</li> <li>• Weight: 51.89 kg (114.4 lb)</li> </ul>
Warranty	3-year limited warranty, CRU (customer replaceable unit) for all other units (varies by country) next business day 9am to 5pm (excluding holidays), warranty service upgrades and maintenance are available.

## Why IBM?

IBM is leading the Cognitive and Cloud space—Integrated Cloud capabilities in POWER9 go in line with IBM's cloud strategy and enable to connect current enterprise data with Cloud based AI or Analytics offerings like Watson. IBM gives you best in class on premise Cloud deployment possibilities with this announcement in addition to the off-premise portfolio already maintained. And we're applying that innovation to cognitive infrastructure, helping our customers on their journey to AI.

IBM aligns cutting-edge innovation with enterprise dependability—IBM has over 105 years of aligning continuous innovation with our customers' business needs.

The POWER9 Scale Out family will be the first set of entry servers that will come completely cloud enabled out of the box with integrated PowerVM® Enterprise capabilities. Additional we introduce on chip Analytics and Algorithms helping customers running their workloads at an always optimized processor frequency for performance and throughput. In combination with the memory footprint of 1TB IBM provides right now Systems to clients that are unmatched by competition in terms of security and virtualization capabilities. The affordable Price/Performance of this new server makes it very attractive to current and future customers. Live partition mobility capabilities are built in, to cloud-enable your POWER9 infrastructure and help you migrate from previous Power Systems. Every new S914 also has the option of a temporary PowerVM license for your old server to support a seamless move of workloads to POWER9.

The new S914 has built in security and is ready for current and future security threats.

## For more information

To learn more about the Power System S914 please contact your IBM representative or IBM Business Partner.

Additionally, IBM Global Financing provides numerous payment options to help you acquire the technology you need to grow your business. We provide full lifecycle management of IT products and services, from acquisition to disposition. For more information, visit: [ibm.com/financing](http://ibm.com/financing)



---

© Copyright IBM Corporation 2018

IBM Systems  
New Orchard Road  
Armonk, NY 10504

Produced in the United States of America  
January 2018

IBM, the IBM logo, [ibm.com](http://ibm.com), Power Systems, and POWER are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at [ibm.com/legal/copytrade.shtml](http://ibm.com/legal/copytrade.shtml)

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

NVIDIA, NVIDIA Volta, NVIDIA NVLink are trademarks of NVIDIA Corporation in the United States, other countries, or both.

This document is current as of the initial date of publication and may be changed by IBM at any time. Not all offerings are available in every country in which IBM operates.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT. IBM products are warranted according to the terms and conditions of the agreements under which they are provided.

Actual available storage capacity may be reported for both uncompressed and compressed data and will vary and may be less than stated.



Please Recycle

---