

Tally 4347-i08 multiform printer



Industrial

IBM Compatible Matrix Printer Solutions Built to Last

The Tally 4347-i08 printers represent high throughput print speeds, rugged durability and unsurpassed performance under the most extreme conditions. These workhorse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head. This head is built for long life and a heavy workload so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for the money.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.



Sample Intelligent Mail Barcode

Models Available:

- Tally 4347-i08 - single front tractor printer
- Tally 4347-i08-2T - dual tractors - front and rear

HIGHLIGHTS

- Ethernet (10/100BaseT) and Parallel standard.
- Optional; Coax/Twinax; Cx/Tx IPDS, Ethernet IPDS; RS232 Serial
- Prints up to 9 part forms
- Full range of automatic features to minimize user intervention
- Ideal for On-Demand and Batch applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Automatic forms loading and thickness adjustment
- Compatible with a wide range of IBM systems, using interfaces and protocols developed and tested in many installations worldwide

The Right Connectivity, and Easy to Operate

These products are well matched to IBM systems applications, with a wide range of connectivity compatible with most IBM printers.

Fully automated operation, coupled with the straight through paper path, allows ease of use and virtually eliminates errors caused by user intervention.



DASCOM

Tally 4347-i08 multiform printer

Print Speed	High Speed Draft: 12cpi->840cps 10cpi->700cps
Throughput	587 pages per hour (ECMA 132)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128Kb
Standard Connectivity	Ethernet 10/100BaseT, Bi-directional parallel
Optional Connectivity	RS232 Serial, Twinax/Coax, Tx/Cx IPDS, Ethernet IPDS
Standard Emulation	IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Fonts	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP, Intelligent Mail Bar Code
Consumables	Ribbon: 20 million characters
STD Paper Handling	Push tractor with paper parking and auto gap adjust
Optional Paper Handling	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device
Paper Type	Continuous forms
Paper Weight	60-120gsm
Paper Size	Length: 3 min, 22 max Width 3 min, 16.5 max
Physical Weight	Approximately 42 lbs
Physical Size	(HxWxD): 11.0 x 24.6 x 17.0 inches
Power Voltage	AC 230V and 120V (selectable)
Power Consumption	60W printing
Workload	48,000 pages per month
Number of Copies	Up to 9 part forms
Temperature	+10° to +35°C (+50° to +90°)
Humidity	20% to 80%
Acoustics	59dB(A)
Warranty	One year on site, next business day